

BACKHOES

FARMTRAC

DRIVING TRADITIONS TOMORROW



BACKHOES

Smooth precision control for optimum work efficiency with compact and utility tractors



Phil 973-383-3592
BRODHECKER FARM
 2Branchville-Lawson rd Newton, NJ 07860
www.brodheckerfarms.com

BACKHOE SPECIFICATIONS

MODELS

	4007	4008	4009	4010
Suitable for Farmtrac Tractor Models	2700TC, 3000TC, 3200TC, 3600TC, 390HST	2700TC, 3000TC, 3200TC, 3600TC, 390HST	All 2-Wheel and 4-Wheel Drive Utility Tractor Models	All 2-Wheel and 4-Wheel Drive Utility Tractor Models
Digging Depth	6 ft. 6 in.	7 ft. 6 in.	9 ft.	10 ft. 6 in.
Transport Height (in.)	64.5	71	86	124
Clearance Height (in.)	58.5	59	83	114
Loading Reach (in.)	44	49	100	112
Ground Clearance (in.)	17	12	17	15
Reach from Center Line of Tire to Center Line of Swing Pivot (in.)	50.5	52	52	39
Reach from Center of Swing Mast to Pivot Point (in.)	98	105	125	167
Stabilizer Spread, Operating Position (in.)	88	88	84	129
Stabilizer Spread, Transport Position (in.)	54	54	74	64
Bucket Rotation (degrees)	164.5	153	142	104
Swing Arc (degrees)	180	180	180	180
Bucket Digging Force (lbs.)	2850	2850	5000	6200
System Relief Valve Setting (PSI)	2200	2200	2550	2500
Swing Circuit Relief Valve Setting (PSI)	2200	2200	2550	2500
Maximum Hydraulic Flow (GPM)	6.5	6.5	10	10
Mounting Kit Options	3-Point Hitch or Sub-Frame 12/16/18/24/36 PTO Pump Kit	3-Point Hitch or Sub-Frame 12/16/18/24/36 PTO Pump Kit	3-Point Hitch or Sub-Frame 12/16/18/24/36 PTO Pump Kit	3-Point Hitch or Sub-Frame 12/18/24/28/36 PTO Pump Kit
Bucket Width Options (in.)				
Other Options Available				



FIVE BUCKET WIDTHS
 12/16/18/24/36 inch buckets available to match your job demands

Boom Extension and Swing Arc
 Left Stabilizer



CONTROL PANEL
 Designed for smooth, precision control and optimum work efficiency

Dipper Extension and Bucket Curl
 Right Stabilizer



FLOATING STABILIZERS
 Floating action assures stabilizer pads make full contact with uneven, difficult terrain

Farmtrac North America, LLC

PO Box 1139

Tarboro, NC 27886

1.877.639.5194

Farmtrac.com