

300DTC/360DTC

FARMTRAC

DRIVING TRADITIONS TOMORROW



300DTC 4WD

30HP, 12 Speed
Synchro-Shuttle

360DTC 4WD

39HP, 12 Speed
Synchro-Shuttle



FRONT-END LOADER

TLB PACKAGE

GROOMING MOWER



Other matching implements available

300DTC/360DTC SPECIFICATIONS

PERFORMANCE

| | |
|-----------------|---------------------------|
| Gross Engine HP | 30 (300DTC) / 39 (360DTC) |
| Max. PTO HP | 26 (300DTC) / 33 (360DTC) |

ENGINE

| | |
|--------------|--|
| Type | 4-Stroke, Indirect Injection, Water-Cooled |
| Cylinders | 4 |
| Displacement | 91.5 (300DTC) / 107.3 (360DTC) cu. in. |
| Battery | 12-Volt (600 CCA) |
| Alternator | 50 Ampere |
| Air Cleaner | Dry Type, with Replaceable Cartridge |

CLUTCH

| | |
|------|-------------------|
| Type | Dry, Single Stage |
| Size | 9.5 in. |

TRANSMISSION

| | |
|--------|---------------------------------|
| Type | Shuttle Drive, Full Synchronesh |
| Speeds | 12 Forward & 12 Reverse |

BRAKES

| | |
|---------------|-----------------|
| Type | Wet, Multi Disc |
| Parking Brake | Hand Lever |

POWER TAKE OFF

| | |
|-------|--|
| Type | Independent or Manual, Switch Operated |
| Speed | 540 rpm @ 2520 Engine rpm |

STEERING

| | |
|------|-------------|
| Type | Hydrostatic |
|------|-------------|

HYDRAULICS

| | |
|----------------------|--|
| Type | Automatic Draft, Position & Mixed Control with Flow & Response Control |
| Type of Linkage | 3-Point, Cat I |
| Lifting Capacity | 2976 lbs. (24 in. Behind Hitch Point) |
| Total Hydraulic Flow | 11.9 (300DTC) / 12.2 (360DTC) gpm |
| - Implement Pump | 7.8 (300DTC) / 8.1 (360DTC) gpm |
| - Steering Pump | 4.1 gpm |
| Auxiliary Valves | Two, Double Acting with Four Outlets |

DIMENSIONS & WEIGHTS

| | |
|----------------|--|
| Overall Length | 126 in. |
| Overall Width | 66 in. |
| Overall Height | 88 in. (to Top of Rollbar) |
| Track Width | Front 46 in. (Fixed) Rear 43.5-53.4 in. (7 Positions) |
| Net Weight | 3050 lbs. |

STANDARD FEATURES

Foldable Rollbar, Telescopic Drawbar, Rear Differential Lock, and Adjustable Stabilizers

OPTIONAL FEATURES

Wafer Weights and Front Grille Guard

TIRES

| | Ag | Turf | Industrial |
|------------|----------------|---------------|------------|
| 4WD Ag | F: 8.3 X 16 | R: 12.4 X 24 | |
| Industrial | F: 27 X 8.5-15 | R: 43 X 16-20 | |
| Industrial | F: 10 X 16.5 | R: 420/70-24 | |
| Turf | F: 25 X 10.5 | R: 41 X 14-20 | |

360DTC
4WD



Shuttle Drive Lever Conveniently Located

4-cylinder
Mitsubishi Engine

300DTC
4WD



Two Sets of Remote Outlets

Switch Operated Electrohydraulic PTO

Foldable Rollbar

See Your Local Dealer

Phil @ 973-383-3592
BRODHECKER FARM
2 Branchville-Lawson Rd.
Newton, NJ 07860

Farmtrac North America, LLC

PO Box 1139

Tarboro, NC 27886

1.877.639.5194

Farmtrac.com

©2005 Farmtrac North America, LLC

Specifications and design subject to change without notice.

FT300/360-05-A